

# MINIpowerPLUS

(1.25–10 kVA)

## Technical Specification



# MINIpowerPLUS

## All models

Input voltage (nominal)	230V									
Input frequency	50/60Hz $\pm$ 2% autosensing									
Input voltage range	184 to 264V at 100% load, 100 to 264V at 50% load									
Input power factor	>0.99 at 20% load									
Input current total harmonic distortion	<3%									
Output voltage	230V $\pm$ 1%									
Output frequency	50/60Hz synchronised									
<b>Overload capacity</b>										
Online modes	150% for 30s, 200% for 5s, 300% for 1s									
Battery modes	160% for 15s									
Protection degree	IP 21									
Standards	EN62040-1, EN50091-2, EN62040-3									
Batteries	3 x 12V 9 Ah sealed lead-acid, maintenance-free batteries per board (standard) Up to several hours available on request									
<b>MINIpowerPLUS tower</b>	<b>5000</b>					<b>10000</b>				
Rated power (kVA)	1.25	2.5	3.75	5	5	6.25	7.5	8.75	10	
Active power (kW)	0.875	1.75	2.625	3.5	3.5	4.375	5.25	6.125	7	
Dimensions (mm) WxDxH	270 x 475 x 570					270 x 475 x 570				
Weight (kgs)	23.5	34	43	53	24	26.5	29	31.5	34	
Battery	Internal (external optional)					External (additional cabinets)				
<b>MINIpowerPLUS rack</b>	<b>5000</b>									
Rated power (kVA)	1.25	2.5	3.75	5						
Active power (kW)	0.875	1.75	2.625	3.5						
Dimensions (mm) WxDxH	483 x 600 x 266			(6 U)						
Weight (kgs)	23.5	34	43	53						
Battery	Internal (external optional)									

---

**Uninterruptible Power  
Supplies Ltd,**

Woodgate,  
Bartley Wood Business Park,  
Hook, Hampshire RG27 9XA

---

**Tel:** 01256 386700

---

**Fax:** 01256 386701

---

**Email:** [sales@upspower.co.uk](mailto:sales@upspower.co.uk)

---

